

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Trennmittel

Print date: 16.02.2015

Product code: NON_STICK

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trennmittel

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Company name:	Hager und Werken GmbH & Co. KG	
Street:	Ackerstrasse 1	
Place:	D-47269 Duisburg	
Telephone:	+49 203 992690	Telefax: +49 203 299283
e-mail:	info@hagerwerken.de	
Internet:	www.hagerwerken.de	
Responsible Department:	Produktsicherheit	

1.4. Emergency telephone number: +49 203 992690 Mo. - Do. 8:00 - 16:30 Fr. 8:00 - 14:00

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Indications of danger: F+ - Extremely flammable, Xi - Irritant, N - Dangerous for the environment

R phrases:

Extremely flammable.

Irritating to skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

GHS classification

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Hazardous components which must be listed on the label**

Hydrocarbons, C6, isoalkane, <5% n-hexane

Signal word: Danger

Pictograms: GHS02-GHS07-GHS09

**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P501	Dispose of contents/container to Dispose of this material and its container to hazardous or special waste collection point..

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Trennmittel

Print date: 16.02.2015

Product code: NON_STICK

Page 2 of 8

P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P271	Use only outdoors or in a well-ventilated area.
P251	Do not pierce or burn, even after use.
P210	Keep away from heat. No Smoking.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
265-151-9	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	25-50 %
64742-49-0	F - Highly flammable, Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R11-38-51-53-65	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411	
01-2119484651-34		
203-448-7	butane	25-50 %
106-97-8	F+ - Extremely flammable R12	
601-004-00-0	Flam. Gas 1; H220	
200-827-9	propane	10-25 %
74-98-6	F+ - Extremely flammable R12	
601-003-00-5	Flam. Gas 1; H220	

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

If swallowed, immediately drink: Water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

Unsuitable extinguishing media

Water. Foam. Water with tenside additive. Water.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Trennmittel

Print date: 16.02.2015

Product code: NON_STICK

Page 3 of 8

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

Further information on handling

No data available

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition.
- No smoking.

Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

Further information on storage conditions

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Additional advice on limit values

No data available

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Trennmittel

Print date: 16.02.2015

Product code: NON_STICK

Page 4 of 8

**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

Test method**Changes in the physical state**

Initial boiling point and boiling range:	-0,5 °C
Flash point:	< 0 °C
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	9,4 vol. %
Ignition temperature:	300 °C
Vapour pressure: (at 20 °C)	2100 hPa
Vapour pressure: (at 50 °C)	4900 hPa
Density:	0,725 g/cm ³

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Trennmittel

Print date: 16.02.2015

Product code: NON_STICK

Page 5 of 8

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
106-97-8	butane	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS

Irritation and corrosivity

Vapours may cause drowsiness and dizziness. After skin contact: Irritant.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing dangerous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Trennmittel

Print date: 16.02.2015

Product code: NON_STICK

Page 6 of 8

substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 625
 Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: See SP277
 EmS: F-D, S-U

Other applicable information (marine transport)

E0

Air transport (ICAO)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Trennmittel

Print date: 16.02.2015

Product code: NON_STICK

Page 7 of 8

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
 Hazard label: 2.1



Special Provisions: A145 A167
 Limited quantity Passenger: 30 kg G
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

E0
 : Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

1999/13/EC (VOC): 80 % (520 g/l)

National regulatory information

Water contaminating class (D): 2 - water contaminating

SECTION 16: Other information**Full text of R phrases referred to under Sections 2 and 3**

11 Highly flammable.
 12 Extremely flammable.
 38 Irritating to skin.
 51 Toxic to aquatic organisms.
 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 53 May cause long-term adverse effects in the aquatic environment.
 65 Harmful: may cause lung damage if swallowed.
 67 Vapours may cause drowsiness and dizziness.

Full text of H statements referred to under Sections 2 and 3

H220 Extremely flammable gas.
 H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H229 Pressurised container: May burst if heated.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Trennmittel

Print date: 16.02.2015

Product code: NON_STICK

Page 8 of 8

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)