## **Product Data Sheet**

## According to EU 1907/2006 REACH and GHS/CLP Classification 1272/2008

17.10.19

## **Microfiber Leather Buffing Wheels**



Date of issue: 11.07.16

Date of print:

<b>1. PRODUCT AND COMPANY IDENTIFICATION</b>			
1.1. Product:	Microfiber Leather Buffing Wheels		
1.2. Trade name:	Art. No.: 520		
1.3. Manufacturer:	HATHO GmbH		
	Freiburger Straße 18 D-79427 Eschbach		
	Tel: + 49 (0)7634/5039-0		
	Fax: + 49 (0)7634/5039-22		
	E-mail: info@hatho.de		
1.4. Reference:	Management		
1.5. Emergency telephone number:	Tel: + 49 (0)7634/50390 // E-mail: info@hatho.de		
2. HAZARDS IDENTIFICATION			
2.1. Categorisation of the substance			
product:	Manufacture: Microfiber cloth		
GHS / CLP / EC Rating	Not rated		
-			
2.2. Hazard - labels:	Hazard symbols: none		
	P 280: safety gloves / protective goggles		
2.3. Further hazards:	Index consideration of the visual proposition on (		
2.3. Further hazarus.	Under consideration of the usual precautionary		
	measures, the general accident prevention regulations		
	and correct handling of the safety equipment, there are no particular hazards known.		
3. INGREDIENTS			
3.1. Chemical characterisation	Microfiber cloth		
of the edging material.	Ingredients:		

of the edging material:

Ingredients:

Ingredient	CAS – No.	Content (%)
nylon	25038-54-4	65
polyurethane	61789-63-7	35

<b>3.2. HAZARDOUS INGREDIENTS:</b>	NONE	
4. FIRST AID MEASURES		
4.1. General notes:	See VBG 103	
4.2. Inhalation:	Not possible, because of the products size	
4.3. Skin contact:	Product is generally not skin irritating, if signs / symptoms develop get medical attention	
4.4. Eye contact:	Flush eyes with large amounts of water, if signs / symptoms persist get medical attention	
4.5. If swallowed:	Get medical attention	
4.6. Information for the physician:	NONE	
5. FIRE FIGHTING MEASURES		
5.1. Eligible extinguishing media:	Water, sand, foam etc.	
5.2. For safety reasons		
not eligible extinguishing media:	None known	
5.3. Special hazards due to the substance or its combustion		
products:	None known	
5.4. Special safety equipment:	None known	
5.5. Additional information:	None known	

	Product Data Sheet		
According to EU 1907/2006 REACH			
and GHS/CLP Classification 1272/2008	Microfiber Leather		
Date of issue: 11.07.16	Microfiber Leather Buffing Wheels		
Date of print: 17.10.19			
6. ACCIDENTAL RELEASE MEASURES			
6.1. Individual-related safety measure	S:		
6.2. Environmental safety measures:	No negative ecological effects known		
6.3. Cleaning measures:	Grab mechanically		
6.4. Additional information:	No dangerous substances are being discharged		
7. HANDLING AND STORAGE 7.1. Handling:	Information for acquire handling acc V/PC 40		
7.1. Handing.	Information for secure handling: see VBG 49 Personal safety equipment: protective goggles		
	Hand guard: safety gloves, only for long and intensive skin contact		
	Breathing protection: vacuum the polishing abrasion automatically		
7.2. Storage:	Requirements for storage areas and containers: only use		
	containers, which are specifically suited for the product		
	store in areas with sufficing ventilation		
8. EXPOSURE CONTROL AND PERSONAL PR			
8.1. Additional information for the arrangements			
	Note: pay attention to the general regulations for accident prevention		
of technical construction:			
	Note: pay attention to the general regulations for accident prevention especially the maximal peripheral surface speed and number of revolutions		
of technical construction:	especially the maximal peripheral surface speed and number of revolutions		
	especially the maximal peripheral surface speed and number of revolutions		
of technical construction: 8.2. Components with workplace relat	especially the maximal peripheral surface speed and number of revolutions ed limit values:		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment:	especially the maximal peripheral surface speed and number of revolutions		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 solid		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 solid yellow		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 solid yellow scentless		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 solid yellow scentless very unlikely, if product is used properly		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C :	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none none none		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none none not available insoluble		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C : 9.8. Solubility in water at T = 20°C :	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none none none		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C : 9.8. Solubility in water at T = 20°C : 9.9. PH-value:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none none none not available insoluble 0,5		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C : 9.8. Solubility in water at T = 20°C : 9.9. PH-value: 9.10. Viscosity: 9.11. Flashpoint: 9.12. Thermal decomposition:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none none none not available insoluble 0,5 not applicable		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C : 9.8. Solubility in water at T = 20°C : 9.9. PH-value: 9.10. Viscosity: 9.11. Flashpoint:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none not available insoluble 0,5 not applicable not applicable		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C : 9.8. Solubility in water at T = 20°C : 9.9. PH-value: 9.10. Viscosity: 9.11. Flashpoint: 9.12. Thermal decomposition:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none not available insoluble 0,5 not applicable not applicable		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C : 9.8. Solubility in water at T = 20°C : 9.9. PH-value: 9.10. Viscosity: 9.11. Flashpoint: 9.12. Thermal decomposition: 9.13. Additional information: 10. STABILITY AND REACTIVITY 10.1. Avoid these conditions:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none not available insoluble 0,5 not applicable not applicable none		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C : 9.8. Solubility in water at T = 20°C : 9.9. PH-value: 9.10. Viscosity: 9.11. Flashpoint: 9.12. Thermal decomposition: 9.13. Additional information: 10. STABILITY AND REACTIVITY 10.1. Avoid these conditions: 10.2. Avoid these substances:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none not available insoluble 0,5 not applicable not applicable none none		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C : 9.8. Solubility in water at T = 20°C : 9.9. PH-value: 9.10. Viscosity: 9.11. Flashpoint: 9.12. Thermal decomposition: 9.13. Additional information: 10. STABILITY AND REACTIVITY 10.1. Avoid these conditions:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none none none not available insoluble 0,5 not applicable not applicable none none		
of technical construction: 8.2. Components with workplace relat 8.3. Individual safety equipment: 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1.1. Form: 9.1.2. Colour: 9.1.3. Odour: 9.2. Combustibility: 9.3. Melting point: 9.4. Self ignition: 9.5. Explosion hazard: 9.6. Explosion range: 9.7. Density at T = 20°C : 9.8. Solubility in water at T = 20°C : 9.9. PH-value: 9.10. Viscosity: 9.11. Flashpoint: 9.12. Thermal decomposition: 9.13. Additional information: 10. STABILITY AND REACTIVITY 10.1. Avoid these conditions: 10.2. Avoid these substances:	especially the maximal peripheral surface speed and number of revolutions ed limit values: See 7.1 Solid yellow scentless very unlikely, if product is used properly nylon 220°C, polyurethane 220°C none none none none not available insoluble 0,5 not applicable not applicable none none		

Product Data Sheet						
According to EU 1907/2006 REACH and GHS/CLP Classification 1272/2008		Microfiber Leather	hatho			
Date of issue: Date of print:	11.07.16 17.10.19	Buffing Wheels	hatho			
11. TOXICOLOGICAL INFORMATION         11.1. Acute toxicity:       none known         11.2. Sub acute / chronically toxicity:       none known						
<ul> <li>12. ECOLOGICAL INFORMATION         <ul> <li>12.1. Elimination information             (persistency and decomposability) Water endangerment class: 0 (self assigned)</li> <li>12.2. Behaviour in environment compartments</li> <li>12.3. Eco toxicological effects</li> <li>12.4. Additional ecological information</li> </ul> </li> </ul>						
	CONSIDERATIONS	<b>-</b>				
13.1. Pro	duct:	Recommendation: collect waste and hand it over to you disposal partner				
13.2. Pac	ckaging:	Recommendation: cardboard, recyclable				
14. TRANSPOR 14.1. Rec	T INFORMATION gulations:	No hazardous material in terms of transport regulations				
15. REGULATO	RY INFORMATION					
15.1. Lab	pels:	P 280: safety gloves / protective g See 2.2	loggles			
15.2. Nat	ional regulations:	CLP - Classification (EG) 1272/2008				

**Draduat Data Shaat** 

## **16. ADDITIONAL INFORMATION**

THIS MATERIAL DATA SHEET IS PROVIDED AS A COURTESY FOR OUR CUSTOMERS.

**THIS PRODUCT IS NOT REGULATED**, AND A MATERIAL DATA SHEET IS NOT REQUIRES FOR THIS PRODUCT BY THE OSHA HAZARD COMMUNICATION STANDARD.

**THE INFORMATION IN THIS MATERIAL DATA SHEET** IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. THIS MATERIAL DATA SHEET OFFERS ASSISTANCE FOR A SAFE HANDLING OF OUR PRODUCTS, ALTHOUGH THE USER IS RESPONSIBLE FOR DETERMINING WHETHER THIS PRODUCT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR THE USER`S METHOD OF USE OR APPLICATION.

**HATHO MAKES NO WARRANTIES**, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.

**HATHO PROVIDES INFORMATION IN ELECTRONIC FORM** AS A SERVICE TO ITS CUSTOMERS. DUE TO THE REMOTE POSSIBILITY THAT ELECTRONIC TRANSFER MAY HAVE RESULTED IN ERRORS, OMISSIONS OR ALTERATIONS IN THIS INFORMATION, HATHO MAKES NO REPRESENTATIONS AS TO ITS COMPLETENESS OR ACCURACY. IN ADDITION, INFORMATION OBTAINED FROM A DATABASE MAY NOT BE AS CURRENT AS THE INFORMATION IN THE MATERIAL DATA SHEET AVAILABLE DIRECTLY FROM HATHO.